

# MATERIAL SAFETY DATA SHEET

## SECTION I MANUFACTURER IDENTIFICATION

Manufacturer's  
Name:

Date of preparation: 5/1/10  
Supercedes; 4/1/07

WAHOO INTERNATIONAL, Inc.  
2605-D Oceanside Blvd  
Oceanside, CA 92054  
(760) 967-7873 fax(760) 967-0146

24-hour EMERGENCY PHONE 800 875-3833

## SECTION II PRODUCT IDENTIFICATION

Product name: Neo-Rez

Product Code:74200 (2.8 oz. tube)

Generic name: Resin, Coating Solution (UN1139)

## SECTION III HAZARDOUS INGREDIENTS

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM: HEALTH FLAMMABILITY REACTIVITY  
2 3 0

**\*WARNING\*** THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO  
THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH  
DEFECTS OR OTHER REPRODUCTIVE HARM. (\*Toluene)

Chemical Identity	WT.%	CAS	ACGIH OSHA	
			TLV	PEL
Resins	27-30%	n/a	n/a	n/a
VM&P Naptha	27-30%	64742-48-9	300ppm	500ppm
Hexane	15-18%	110543	400ppm	500ppm
Toluene	12-14%	108-88-3	100ppm	200ppm
Methyl Ethyl Ketone	22-24%	78-93-3	350ppm	350ppm

## SECTION IV PHYSICAL DATA

BOILING POINT: 160°F PERCENT VOLATILE BY VOLUME: 71.3%

SPECIFIC GRAVITY: 0.94 EVAPORATION RATE (n-Bu Ac = 1): 6.8

VAPOR DENSITY (air=1) 4.6 VAPOR PRESSURE (mm HG @ 68°F): 118

VOC Content: 4.7 lbs/gal.

APPEARANCE AND ODOR: Light straw color. Hydrocarbon odor

SOLUBILITY IN WATER: Insoluble

## SECTION V FIRE AND EXPLOSION DATA

FLASH POINT: 24°C TCC-ASTM D-93

OSHA CLASSIFICATION: IC

FLAMMABLE LIMITS % BY VOLUME IN AIR @ 212°F:

LOWER EXPLOSION LIMIT - 1.10

UPPER EXPLOSION LIMIT - 10.50

EXTINGUISHING MEDIA: Use foam, carbon dioxide or chemical fire fighting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: This material is flammable and may be ignited by heat, fire, sparks and/or static electricity.

SPECIAL FIRE FIGHTING PROCEDURES: The use of self-contained breathing apparatus is recommended for fire-fighters. Water spray may be used for cooling containers in order to prevent possible pressure build-up and auto-ignition.

=====**SECTION VI HEALTH HAZARD DATA**=====

THRESHOLD LIMIT VALUE: see section III

EFFECTS OF OVEREXPOSURE:

- EYES: Irritation, redness, tearing and blurred vision.
- SKIN: Moderate irritation, defatting, dermatitis and sensitization.
- INHALATION: Nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and headache. High concentration may result in narcosis (CNS depression).
- INGESTION: G.I. irritation, nausea, vomiting and diarrhea.

EMERGENCY AND FIRST AID PROCEDURES

- EYES - Flush with clean, warm water for at least 15 minutes occasionally lifting eyelids.
- SKIN - Remove contaminated clothing. Wash affected areas with soap and water.
- INHALATION- Remove to fresh air. Apply artificial respiration or administer oxygen if necessary. Call a physician immediately.
- INGESTION - Keep person warm, quiet. Get immediate medical attention. Do not induce vomiting. Aspiration of material into lungs can cause chemical pneumonitis.

=====**SECTION VII REACTIVITY DATA**=====

STABILITY: Stable under normal conditions.

INCOMPATIBILITY: Avoid contact with strong acids, bases and oxidizing agents.

**Section VII cont.**

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield carbon dioxide, carbon monoxide possibly phosgene and hydrogen chloride.

=====**SECTION VIII SPILL OR LEAK PROCEDURES**=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Cover spill with inert absorbent material and shovel with non-sparking tools into container. Remove container to a safe area and seal.

WASTE DISPOSAL METHOD:

Waste disposal must be disposed of in accordance with federal, state, and local environmental regulatory controls.

=====SECTION IX SPECIAL PROTECTION INFORMATION=====

RESPIRATORY PROTECTION: Avoid breathing vapor or mist. If exposure does exceed occupational limits (see section III), use a NIOSH-approved respirator to prevent overexposure. In accordance with 29CFR 1910.134, use either a full-face, atmosphere-supplying respirator or air-purifying respirator for organic vapors.

VENTILATION: Local exhaust must be sufficient to keep airborne vapor concentrations below TLV limit (see section III). Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PROTECTIVE GLOVES: Impervious clothing / boots as needed.

EYE PROTECTION: Splash goggles.

=====SECTION X TRANSPORTATION=====

<u>D.O.T. Proper Shipping Name</u>	<u>UN #</u>	<u>Class</u>	<u>Hazard</u>	<u>P.G.</u>	<u>Pkg instr.</u>	<u>Max net/pkg.</u>	<u>IATA</u>
"COATING SOLUTION"	1139	3	Flammable Liquid		II309	60L./220L.	pass./cargo

<u>If Consumer Commodity,</u>	<u>I.D.#</u>	<u>Class</u>	<u>qualifying chem.</u>	<u>Pkg. Instr.</u>	<u>Max Gross</u>
"CONSUMER COMMODITY"	8000	9	Petroleum Naptha	910	25 Kg.